

**INSTRUCTIONS TO MODIFY A 2-A AND 2-B RECEIVERS FOR A BAND
COVERAGE OF FREQUENCIES 1.8 to 2.0 KC
(Serial Numbers Higher Than 1000 Only)**

This modification will be performed at the factory for a charge of \$12.50. This includes all parts, labor and crystal, but does not include shipping charges via Rail Express to or from the Miamisburg.

Field service and modification instructions are intended for execution by competent electronics technicians. Damage resulting from incompetence, carelessness, or negligence will not be covered by our warranty.

1. Remove chassis from cabinet. Lay receiver on its panel, remove the six screws in bottom cabinet, and pull case up, off the rear of chassis.
2. Place chassis upside down on the table with panel toward you. Notice the "T" shaped partition (near the front, right corner) with a band switch wafer on each side and trimmer condenser at right.
3. Install another trimmer identical to the one in the set (Arco part No. 462 5-80 mmf), in the holes provided. Use same method of attachment and be sure that the gnd. And hot lugs are positioned same as the ones on the original trimmer. BE CAREFUL NOT TO MOVE THE SMALL WHITE INCREMENT COILS SOLDERED TO SWITCH WAFER AS ALIGNMENT ON 15 AND 20 METERS WILL BE SPOILED.
4. On each of two switch wafers, remove a jumper wire which runs between 80M contact and A contact (rotate the band switch knob and watch the blade of the rotor to pick out the two contacts on each wafer. The wafers are identical.

While working around the switch wafers with a soldering iron, BE CAREFUL, do not overheat the switch contacts, they will become loose or lose their spring temper. Do not let solder run down the contacts. Do not try to clean the wafer with any solvent.

5. Run a short wire from the A contact of the front wafer to the "hot" term. Of the trimmer.
6. Connect CA (1330 pf silver mica, dipped type preferred) across the terminals of the trimmer.
7. Connect the gnd. Terminal of the trimmer to the grounded wire which runs down from the original trimmer to the wiper lug of the preselector variable condenser.
8. Connect CB (1390 pf silver mica, dipped type preferred) from the A contact of the rear wafer to the coil terminal which is the junction of a 1500 ohm resistor and a 180 mmf dipped mica capacitor.
9. Insert a 5.5 mc for 160 M crystal in the A socket and turn band switch to the A position.