



RESISTANCE READINGS

ITEM	TUBE	Pin 1	Pin 2	Pin 3	Pin 4	Pin 5	Pin 6	Pin 7	Pin 8	Pin 9
V1	6BA6	2.5 meg	0Ω	FIL	FIL	+1500Ω	+47K	0Ω	0Ω	47K
V2	6U8A	+122K	1 meg	+100K	FIL	FIL	+1500Ω	0Ω	47Ω	47K
V3	6U8A	+147K	2.5 meg	+100K	FIL	FIL	+1500Ω	0Ω	0Ω	47K
V4	6U8A	+1490K	2.5 meg	+100K	FIL	FIL	+1500Ω	0Ω	4700Ω	470K
V5	6FM8	1 meg	1.5 meg	1.5 meg	FIL	FIL	1 meg	0Ω	1 meg	+110K
V6	6AQ5	470K	560Ω	FIL	FIL	+900Ω	+500Ω	470K		
V7	6FY5	0Ω	47K	FIL	FIL	+115K	47K	0Ω		
V8	12BY7A	0Ω	47K	0Ω	FIL	FIL	+830Ω	+5500Ω	0Ω	

- ⊖ See parts list for alternate value or application.
- 1. Voltage measurements taken with vacuum tube voltmeter.
- 2. All controls set for normal operation, no signal applied.
- 3. Measured values are from socket pin or terminal to common ground.
- 4. All terminals viewed from bottom unless otherwise designated.
- 5. Numbers assigned to terminals may not be found on the unit.
- 6. Supply voltage maintained at rated value for voltage readings.

A PHOTOFAC STANDARD NOTATION SCHEMATIC
with **CIRCUITRACE**

©Howard W. Sams & Co., Inc. 1963

EICO MODELS 771W, 772W

DOTTED LINES INDICATE CIRCUIT USED IN MODEL 772W