



SEMICONDUCTOR	TERMINAL CONNECTION	VIEW	TERMINAL CONNECTION	VIEW	TERMINAL CONNECTION	VIEW		
25A 719	ECB	TOP VIEW	25C 710	BCE	TOP VIEW	25C 784	ECB	TOP VIEW
25C 828	BCE	TOP VIEW	25C 784	ECB	TOP VIEW	25C 1687	BCE	TOP VIEW
25C 829	BCE	TOP VIEW	25C 1688	BCE	TOP VIEW	25C 1306	BCE	TOP VIEW
25C 829	BCE	TOP VIEW	25C 1306	BCE	TOP VIEW	25C 1678	BCE	TOP VIEW
25C 945	BCE	TOP VIEW	25C 1678	BCE	TOP VIEW	25C 1816	BCE	TOP VIEW
25C 945	BCE	TOP VIEW	25C 1816	BCE	TOP VIEW	25C 1957	ECB	TOP VIEW
25C 1318	BCE	TOP VIEW	25C 1957	ECB	TOP VIEW	TA 7205P	ECB	TOP VIEW
25C 1318	BCE	TOP VIEW	TA 7205P	ECB	TOP VIEW	BA 521	12-90	TOP VIEW
25C 1047	BCE	TOP VIEW	BA 521	12-90	TOP VIEW			
25C 1215	BCE	TOP VIEW						

- NOTES:**
- All resistors are 5%, 1/4 watt, with value given in ohms, unless specified otherwise.
  - All capacitor values are given in uF, unless specified otherwise.
  - Symbols used:  
 ⊕ - chassis ground  
 ⊕ - p.c. board ground  
 \* - indicates component value may vary from unit to unit

Figure 2-12. Schematic Diagram, Model 2701X